



**Certificate of conformity of the factory  
production control  
according to AVCP System 2+**

**0763 - CPR - 6079**

**MPA | Eberswalde**

Materialprüfanstalt  
Brandenburg GmbH

Prüfung, Überwachung,  
Zertifizierung, Gutachten,  
Forschung und Entwicklung

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Plywood for use as structural components in humid conditions,  
technical class EN 636-2 S  
from hardwood "Homogen" or  
hardwood and softwood "Combi",  
thickness from 9 mm to 50 mm**

Alfred-Möller-Straße 1, H 13  
D-16225 Eberswalde

Fon +49 (0) 33 34. 65 560  
Fax +49 (0) 33 34. 65 550

www.mpaew.de  
office@mpaew.de

Geschäftsführer:  
Dr. Peter Schumacher

HRB 10408 FF

produced by the manufacturer

**PAGED Pisz Sp. z.o.o.  
ul. Kwiatowa 1; PL – 12-200 Pisz**

and produced in the manufacturing plant

**PAGED Pisz Sp. z.o.o.  
ul. Kwiatowa 1; PL – 12-200 Pisz**

**This certificate attests that all provisions concerning the assessment and  
verification of constancy of performance described in Annex ZA of the  
standard**

**EN 13 986 : 2004 + A1:2015**

**under system 2+ are applied and that**

**the factory production control fulfils all the prescribed  
requirements set out above.**

This certificate was first issued on 07<sup>th</sup> of January 2020 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product and the manufacturing conditions in the plant are not modified significantly and only with consideration in the annex 1 and 2 to this certificate and in the monitoring reports by the certification body given editions and references.

Eberswalde, 07<sup>th</sup> of January 2020



Dr. rer. nat. R. Wegner  
Head of the Certification-Office

Sparkasse Schwandorf  
Kto-Nr.: 100 164 862  
BLZ: 750 510 40  
IBAN: DE55 7505 1040 0100 1648 62  
BIC-/SWIFT: BYLADEM1SAD  
USt.-Id. DE814335485  
Finanzamt Eberswalde



Die Akkreditierung gilt nur für die in der Urkunde aufgeführten Verfahren.



vom DIBt anerkannte  
PUZ-Stelle BRA02



EC notified 0763



CARB notified TPC 18

**Annex 2 to certificate 0763-CPD-6079 (Version 07.01.2020)**

**Design of the CE marking**

|                                                                                                                                                                                                                         |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>0763 - CPR - 6079</b>                                                                                                           |
| <b>PAGED PISZ Sp. z.o.o.</b><br><b>&lt;20&gt;*</b><br><b>DOP-000X-2020/01/07</b>                                                                                                                                        |
| <b>EN 13 986:2004+A1:2015</b><br><b>EN 636</b><br><b>Class EN 636-2 S &lt;thickness&gt;** mm</b><br><b>&lt;factory typ&gt;</b><br><b>E 1</b><br><br><b>Reaction to fire class: D-s2, d0***</b>                          |
| if possible supplementary properties<br>in accordance with EN 636, for example:<br>capture 4 classes of bending properties,<br>capture 5 and also table A.1, surface layer,<br>kind of wood, use class acc. to EN 335-3 |

- \* year of production this panel  
\*\* thickness of this panel, from 9 mm up to 50 mm  
\*\*\* acc. to EN 13986 table 8

**Marking panels**

**CE NB-number <factory-key> <Reference number of DoP>**  
**EN 13 986:2004+A1:2015 <technical class> <thickness> mm <Reaction to fire class> <formaldehyde-class> <production-key> (charge-number or date of production)**

Example: CE\_0763\_PS-Pisz\_DOP-00001-2020/01/07\_  
EN 13 986:2004+A1:2015\_EN 636-2 S\_50 mm\_D-s2, d0\_E1\_20200107