Paged Durable

Paged Durable is produced from high quality Baltic birch plywood coated with a polypropylene layer. The final panel offers extra protection against moisture and UV radiation, simultaneously ensuring colour fastness. Available with a smooth or orange peel finish to match your desired application.

KEY BENEFITS AND APPLICATIONS

- Main application areas include: Trailer walls and fit-out, horse trailers, retail shelving units, retail and commercial space fitout, furniture, transportation
- Colour fastness ≥ 6 (EN ISO 105-B02)
- Resistance to cracking
- Long life-span
- Manufactured from sustainable resources in Poland

STANDARD SIZES [mm]

*Other formats available on request

DIMENSIONAL DEVIATION AS PER EN 315 & EN 324

Length/Width	Deviation
< 1000 mm	± 1 mm
1000 – 2000 mm	± 2 mm
> 2000 mm	± 3 mm

STRAIGHTNESS AND SQUARENESS DEVIATION AS PER EN 315 & EN 324

	Deviation
Straightness	± 0,1% or ± 1mm/m
Squareness	± 0,1% or ± 1mm/m

COATING

Туре	Polypropylene
Thickness	0,18 mm
Colour*	White, grey
RAL	9016, 7040
Taber Test	1800 (no. of cycles)

*other colours available on request

RELEASE OF FORMALDEHYDE (EN 717-1) BONDING QUALITY (EN 314-2) MACHINING ADDITIONAL INFORMATION ^½ E1 Class 3 Edge machining, CNC machining and drilling on request 1. General Terms of Sales available from www.skleikapaged.pl 2. Declaration of Performance available from www.skleikapaged.pl 2. Declaration of Performance available from www.skleikapaged.pl

Our product is made of renewable resource. Our products are characterized by low carbon footprint and are produced from certified wood, thus respecting the natural environment and the local community. The information contained in this document is intended as a guideline only and comes without warranty. We reserve the right to amend product specification sheets without notice.

NOMINAL THICKNESS WITH STANDARD DEVIATION, NUMBER OF PLIES, DENSITY AS PER EN 315, EN 323 & EN 324

Density avg. (kg/m³)	Weight (kg/m²) 4,5	Standard Deviation (mm)		Number of plies (pcs)	Nominal Thickness (mm)*
		+0,4	-0,6	5	6,5
_	6,3	+0,5	-0,7	7	9
_	8,4	+0,6	-0,8	9	12
_	10,5	+0,7	-0,9	11	15
640-760** 	12,6	+0,7	-0,9	13	18
	14,7	+0,8	-1,0	15	21
	16,8	+0,9	-1,1	17	24
	18,9	+1,4	-1,8	19	27
	21	+1,5	-1,9	21	30

*Other thicknesses available upon request

**As measured at 8-12% moisture content

n] 1250x2500 1500x2500/3000 1525x3050

(F



The mark of responsible forestry



Our product is made of renewable resource. Our products are characterized by low carbon footprint and are produced from certified wood, thus respecting the natural environment and the local community. The information contained in this document is intended as a guideline only and comes without warranty. We reserve the right to amend product specification sheets without notice.