

DECLARATION OF CONFORMITY, No DoC-HW FR-02

- 1. Identification code of the product-type:**
Structural hardwood plywood, uncoated, 12-30 mm.
- 2. Intended uses:**
For uncoated and surface unprotected plywood as a structural component according to EN 636-2.
- 3. Manufacturer:**
Paged Pisz Sp. z o.o.
ul. Kwiatowa 1
12-200 Pisz
- 5. System of AVCP:**
AVCP system 1
- 6a. Harmonized standard:**
EN 13986:2004+A1:2015, EN 13501-1:2019-02

Paged Pisz
ul. Kwiatowa 1
12-200 Pisz, Poland
UK 0836-CPR-22/P6318

Notified body

British Board Of Agrément (Approved body No 0836)
Bucknalls Lane
Watford
Hertfordshire WD25 9BA

7. Declared performance:

Hardwood plywood			
Essential characteristics	End use condition	min. thickness (mm)	Performance
Reaction to fire			Class (ex. floorings)
		Mechanically fastened to wooden slats, with vertical and/or horizontal joints, ventilated or un ventilated air gap.	12
Essential characteristics	Performance		
Water vapour permeability	Wet cup μ - 90 Dry cup μ - 220		
Release of formaldehyde	Class E1		
Content of pentachlorophenol (PCP)	None		
Airborne sound insulation	NPD		
Sound absorption α	Range	α	
	250-500 Hz	0,10	
	1000-2000 Hz	0,30	
Thermal conductivity λ (W/(mK))	0,17		
Bonding quality	Class 3		
Biological durability	Uncoated or coated and unprotected	Use class 2	
Embedment strength	NPD		
Air permeability	NPD		
Racking resistance	NPD		
Density range (kg/m ³)	680-840		

Harmonized standard EN 13986+A1:2015


Nominal thickness	12	15	18	21	24	27	30
Essential characteristics	Performance						
Bending strength class acc. to EN 636							
II	F35	F35	F30	F30	F30		
I	F30	F25	F25	F25	F25		
Characteristic bending strength acc. to EN 636 (N/mm ²)							
f_m II	52	52	45	45	45		
f_m I	45	38	38	38	38		
Characteristic compression strength	NPD						
Characteristic tension strength	NPD						
E class in bending MOE acc. to EN 636							
II	E70	E80		E70	E70		
I	E50	E60		E50	E50		
Mean MOE in bending acc. to EN 636 (N/mm ²)							
E_m II	6300	7200		6300	6300		
E_m I	4500	5400		4500	4500		
Mean MOE in compression and tension	NPD						
Char. panel shear	NPD						
Char. planar shear	NPD						
Mean MOR in panel shear	NPD						
Mean MOR in planar shear	NPD						

Harmonized standard EN 13986+A1:2015

Performance of this product, as identified above, is in conformity with the set declared performances and characteristics. This declaration of conformity is issued in accordance with Regulation EU No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Pisz, POLAND, 1st December 2022



Jarosław Wasiuk
Dyrektor Sprzedaży Eksportowej
Export Sales Director