

DECLARATION OF CONFORMITY, No DoC-HSW FR-01

1. **Identification code of the product-type:**
Structural hardwood plywood with birch face and softwood core, coated, 9-40 mm.
2. **Intended uses:**
For coated and/or surface protected plywood as a structural component according to EN 636-3.
3. **Manufacturer:**
Paged Morąg S.A.
ul. Mazurska 1
14-300 Morąg
5. **System of AVCP:**
AVCP system 2+
- 6a. **Harmonized standard:**
EN 13986:2004+A1:2015, EN 13501-1:2019-02

Paged Morąg
ul. Mazurska 1
14-300 Morąg, Poland
UK 0836-CPR-21/F526

Notified body

British Board Of Agrément (Approved body No 0836)
Bucknalls Lane
Watford
Hertfordshire WD25 9BA

7. Declared performance:

Hardwood plywood with birch face and softwood core			
Essential characteristics	End use condition	min. thickness (mm)	Performance
Reaction to fire	Wood and wood-based panels and substrates of Euroclasses A1 or A2 at least 6 mm thick, having a density $\geq 1800 \text{ kg/m}^3$. Mechanically fixed against the substrate or against battens created a void.	9	Class (floorings)
			Br-s1
Essential characteristics	Performance		
Water vapour permeability	Wet cup $\mu - 70$ Dry cup $\mu - 200$		
Release of formaldehyde	Class E1		
Content of pentachlorophenol (PCP)	None		
Airborne sound insulation	NPD		
Sound absorption α	Range	Sound absorption α	
	250-500 Hz	0,10	
	1000-2000 Hz	0,30	
Thermal conductivity $\lambda \text{ (W/(mK))}$	0,13		
Bonding quality	Class 3		
Biological durability	Uncoated or coated and unprotected	Use class 2	
	Coated with protected edges	Use class 3	
Embedment strength	NPD		
Air permeability	NPD		
Racking resistance	NPD		
Mean density (kg/m^3)	605		

Harmonized standard EN 13986+A1:2015


Nominal thickness	9	12	15	18	21	24	27	30	35	40
Essential characteristics	Performance									
Characteristic bending strength										
$f_m \parallel$	21,3	20,4	36,5	35,1	32,2	33,0	30,1	29,3	30,2	
$f_m \perp$	28,5	33,1	39,3	25,3	31,6	30,5	25,9	27,4	27,0	
Characteristic compression strength	NPD									
Characteristic tension strength	NPD									
Mean MOE in bending										
$E_m \parallel$	5327	5774	10317	9169	8531	7244	8419	8246	7940	
$E_m \perp$	6438	6541	11267	10404	9327	8357	8344	8317	8158	
Mean MOE in compression and tension	NPD									
Char. panel shear	NPD									
Char. planar shear	NPD									
Mean MOR in panel shear	NPD									
Mean MOR in planar shear	NPD									

Harmonized standard EN 13986+A1:2015

Performance of this product, as identified above, is in conformity with the set declared performances and characteristics. This declaration of conformity is issued in accordance with Regulation EU No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Morąg, POLAND, 1st December 2022


Jarosław Wasiuk
Dyrektor Sprzedaży Eksportowej
Export Sales Director